

X30 SUPER – 175cc

(January 2024)

P.N.: CP30179ESC

Technical Data

Design	1-cylinder / 2-stroke
Bore	Ø 63.92 mm
Max. Bore	Ø 64.04 mm
Stroke	54.40 mm
Displacement:	174.56cc (175,5cc max)
Max. Power	43 Hp at 12.000 Rpm
Max. Torque	26 Nm at 10.500 Rpm
Max. Rpm Limit	15.000 Rpm
Lubrication	oil mixture 4,5%
Ignition system	digital
Transmission	dry centrifugal clutch
Cooling system	water cooled
Starting	on-board electric starter
Carb. Model	Tillotson HB-10A (Ø34mm)
Inlet system	reed valve



Main Features

Electric Start - Water Cooled - Reed Valve Admission - Centrifugal Dry clutch - Digital Ignition with Rev. Limiter - Tillotson HB10A Diaphragm carburettor - One Piece Exhaust - Counter Balance Shaft

Accessories

PVL Digital Ignition plant - H.T. coil/Electronic box "N" with vibration dampers - NGK BR10EG - Sparkplug and PVL cap - Centrifugal clutch group with Z12 detachable sprocket – Main Roller Bearings - Tillotson HB-10A (Ø34mm) - Exhaust manifold - Exhaust silencer mod. X30 Super - Electric starter motor with support – Bendix - Cables harness with Start/Stop buttons and connectors - Buttons bracket with safety shield - Battery support with clamps - Velcro strap - Rubber pads for battery

Price

€ 2.970,00 + VAT

Sales Conditions

Delivery:	ex works / IAME S.p.A.
Lead time:	20/30 days from order confirmation
Packing:	at pure cost
Payment terms:	in advance